

# UNITED STATES PATENT AND TRADEMARK OFFICE



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address; COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.		FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/084,654	<del></del>	02/28/2002	Bernhard Mayr	1454.1217	2483	
21171	7590	11/26/2004		EXAMINER		
	STAAS & HALSEY LLP				DANIEL JR, WILLIE J	
	SUITE 700 1201 NEW YORK AVENUE, N.W.			ART UNIT	PAPER NUMBER	
WASHING				2686		
				DATE MAILED: 11/26/2004	4	

Please find below and/or attached an Office communication concerning this application or proceeding.



	Application No.	Applicant(s)	
	10/084,654 MAYR, BERNHARD		0
Office Action Summary	Examiner Art Unit		<del></del>
	Willie J. Daniel, Jr.	2686	
The MAILING DATE of this communication Period for Reply		ith the correspondence address	
A SHORTENED STATUTORY PERIOD FOR REITHE MAILING DATE OF THIS COMMUNICATIO  - Extensions of time may be available under the provisions of 37 CFR after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a  - If NO period for reply is specified above, the maximum statutory per  - Failure to reply within the set or extended period for reply will, by state Any reply received by the Office later than three months after the magnificant patent term adjustment. See 37 CFR 1.704(b).	N. 1.1.136(a). In no event, however, may a life in the statutory minimum of thir iod will apply and will expire SIX (6) MON attite, cause the application to become Ali	reply be timely filed ty (30) days will be considered timely. ITHS from the mailing date of this communicat BANDONED (35 U.S.C. § 133).	tion.
Status			
1) Responsive to communication(s) filed on _			
2a) This action is <b>FINAL</b> . 2b) ⊠ T	his action is non-final.		
3) Since this application is in condition for allo			is
closed in accordance with the practice unde	er <i>Ex parte Quayl</i> e, 1935 C.E	). 11, 453 O.G. 213.	
Disposition of Claims			
4) ☐ Claim(s) 1-9 is/are pending in the application 4a) Of the above claim(s) is/are without 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-9 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and	drawn from consideration.		
Application Papers			
<ul> <li>9)  The specification is objected to by the Exam</li> <li>10)  The drawing(s) filed on 28 February 2002 is. Applicant may not request that any objection to the Replacement drawing sheet(s) including the containing the oath or declaration is objected to by the</li> </ul>	/are: a) accepted or b)⊠ the drawing(s) be held in abeyarection is required if the drawing	nce. See 37 CFR 1.85(a). I(s) is objected to. See 37 CFR 1.121	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for fore a) All b) Some * c) None of:  1. Certified copies of the priority docume 2. Certified copies of the priority docume 3. Copies of the certified copies of the papplication from the International Bur * See the attached detailed Office action for a	ents have been received. ents have been received in A priority documents have been leau (PCT Rule 17.2(a)).	Application No I received in this National Stage	
	•		
Attachment(s)			
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/Paper No(s)/Mail Date 02/28/2002.	Paper No(	Summary (PTO-413) s)/Mail Date Informal Patent Application (PTO-152)	
S Patent and Trademark Office			

Art Unit: 2686

#### **DETAILED ACTION**

1. This action is in response to application filed on 28 February 2002. Claims 1-9 are now pending in the present application.

# Information Disclosure Statement

2. The information disclosure statement (IDS) submitted on 28 February 2002 is in compliance with the provisions of 37 CFR 1.97 and is being considered by the examiner.

### **Drawings**

- 3. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, the
  - a. handover code
  - b. code word

must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description

Art Unit: 2686

of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. The replacement sheet(s) should be labeled "Replacement Sheet" in the page header (as per 37 CFR 1.84(c)) so as not to obstruct any portion of the drawing figures. If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

4. This list of examples is not intended to be exhaustive.

# Claim Rejections - 35 USC § 102

5. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-2, 7, 9 are rejected under 35 U.S.C. 102(b) as being anticipated by Bodin (US 6,122,512).

Regarding Claim 1, Bodin discloses a method for carrying out a handover procedure in a GSM mobile radio system which reads on the claimed "radio communications system" having a base transceiver station (BTS1) which reads on the claimed "first transmitting/receiving unit", a base transceiver station (BTS2) which reads on the claimed "second transmitting/receiving unit" and base transceiver station (e.g., BTS, BTS3) which reads on the claimed "further transmitting/receiving units" (see col. 5, lines 16-30; Fig. 1), comprising:

Art Unit: 2686

switching a connection which reads on the claimed "radio link" connecting a mobile station (MS) and the first transmitting/receiving unit (BS1), to the second transmitting/receiving unit (BS2) (see col. 6, lines 28-36; col. 5, lines 46-51; Figs. 1, 7),

sending a handover access message signal which reads on the claimed "handover signaling message" from the mobile station (MS) to the second transmitting/receiving unit (BS2) in order to set up a connection to the second transmitting/receiving unit (BS2), which handover signaling message contains a HO reference value (control data) which reads on the claimed "code word" identifying a handover procedure, the code word having a value corresponding to a handover code which is reserved for handover procedures in the radio communications system, the handover signaling message being sent via a physical channel, which also carries signaling messages for setting up a radio link to the radio communications system (see col. 6, lines 25-50; col. 5, lines 46-55; col. 5, line 67 - col. 6, line 1; Figs. 1, 7),

checking the code word at one of the further transmitting/receiving units (BTS), when a signaling message (access signal) is received on the physical channel with a code word, the code word being checked to determine whether the value thereof corresponds to the handover code and decide whether the signaling message should or should not be regarded as a handover signaling message (see col. 7, lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines16-22; Fig. 1), where the MS transmits messages to the neighboring base station for handoff and the message is checked for the correct control data, and

identifying the signaling message received at the one of the further transmitting/receiving stations (BTS) as a handover signaling message on the basis of the code word (see col. 7,

Art Unit: 2686

lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines 16-22; Fig. 1), where the MS transmits messages to the neighboring base station for handoff.

Regarding Claim 2, Bodin discloses the method as claimed in claim 1, wherein the handover code is stored in each of the transmitting/receiving units (BTS) (see col. 7, lines 1-4; col. 6, lines 45-46), where the base station (BTS) check for the correct control data (HO reference value) in which the "handover code is stored" would be inherent to verify the correct code,

the value of the code word received with a signaling message is compared with the handover code stored in each of the further transmitting/receiving units (BTS) (see col. 7, lines 1-4; col. 6, lines 45-46; Figs. 1, 7), where the base station (BTS) check for the correct control data (HO reference value) in which the "handover code is stored" would be inherent to verify the correct code,

if the value of the code word matches the handover code, the signaling message is identified as a handover signaling message (see col. 7, lines 1-4; col. 6, lines 45-46; Fig. 7).

Regarding Claim 7, Bodin discloses the method as claimed in claim 1, wherein at least one of the transmitting/receiving units (BTS) is a base station (BTS) (see col. 5, lines 16-22; Figs. 1, 7-8).

Regarding Claim 9, Bodin discloses a handover method for a radio communications system having a first, second and further transceiver units (BTS) (see col. 5, lines 16-30; Figs. 1, 7), comprising:

switching a radio link connecting a mobile station, from the first transceiver unit (BTS1) to the second transceiver unit (BS2) (see col. 6, lines 28-36, col. 5, lines 46-51, Figs. 1),

Art Unit: 2686

sending a handover signaling message from the mobile station to the second transceiver unit in order to set up a connection to the second transceiver unit, which handover signaling message contains a code word identifying a handover procedure, the code word corresponding to a handover code which is reserved for handover procedures in the radio communications system, the handover signaling message being sent via a channel, which also carries signaling messages for establishing a radio link (see col. 6, lines 25–50; col. 5, lines 46-55; col. 5, line 67 - col. 6, line 1; Figs. 1, 7),

checking the code word at one of the further transceiver units (BTS), when a signaling message is received on the channel with a code word, the code word being checked to determine whether there is correspondence with the handover code (see col. 7, lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines 16-22; Fig. 1), where the MS transmits messages to the neighboring base station for handoff and the message is checked for the correct control data, and

identifying the signaling message received at the one of the further transceiver stations (BTS) as a handover signaling message on the basis of the code word (see col. 7, lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines 16-22; Figs. 1, 7), where the MS transmits messages to the neighboring base station for handoff.

Art Unit: 2686

### Claim Rejections - 35 USC § 103

6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 3-6, 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Bodin (US 6,122,512) in view of Demetrescu et al. (hereinafter Demetrescu) (US 6,647,262 B1).

Regarding Claim 3, Bodin discloses the features

the HO reference value which reads on the claimed "value" of a code word received with a signaling message is compared to the handover code (see col. 7, lines 1-6, col. 6, lines 45-46; Fig. 7), where the message is checked for the correct control data,

if the value of the code word matches the handover code, the signaling message is identified as a handover signaling message (see col. 7, lines 1-6; col. 6, lines 45-50; Fig. 7). Bodin fails to disclose having the features wherein the handover code comprises a number of values, values of the handover code, and one of the values of the handover code. However, the examiner maintains that the features wherein the handover code comprises a number of values, values of the handover code, and one of the values of the handover code was well known in the art, as taught by Demetrescu.

In the same field of endeavor, Demetrescu discloses the features wherein the handover reference number (HO\_REFERENCE\_N) which reads on the "handover code" comprises a number of values (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values,

Art Unit: 2686

values of the handover code (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values to indicate handover, and

one of the values of the handover code (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values that is used to indicate handover.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teachings of Bodin and Demetrescu to have the features wherein the handover code comprises a number of values, values of the handover code, and one of the values of the handover code, in order to force handover of a mobile station to a selected cell of a multicell network, as taught by Demetrescu (see col. 2, lines 25-31).

Regarding Claim 4, Bodin discloses the features

the HO reference value which reads on the claimed "value" of a code word received with a signaling message is compared to the handover code (see col. 7, lines 1-6; col. 6, lines 45-46, Fig. 7), where the message is checked for the correct control data,

if the value of the code word matches the handover code, the signaling message is identified as a handover signaling message (see col. 7, lines 1-6, col. 6, lines 45-50; Fig. 7). Bodin fails to disclose having the features wherein the handover code comprises a number of values, values of the handover code, and one of the values of the handover code. However, the examiner maintains that the features wherein the handover code comprises a number of

Art Unit: 2686

values, values of the handover code, and one of the values of the handover code was well known in the art, as taught by Demetrescu.

Demetrescu further discloses the features wherein

the handover reference number (HO\_REFERENCE\_N) which reads on the "handover code" comprises a number of values (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values,

values of the handover code (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values to indicate handover, and

one of the values of the handover code (see col. 4, lines 53-60; col. 6, line 47), where the handover reference number is an 8 bit number which provides a number of values that is used to indicate handover.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to combine the teachings of Bodin and Demetrescu to have the features wherein the handover code comprises a number of values, values of the handover code, and one of the values of the handover code, in order to force handover of a mobile station to a selected cell of a multicell network, as taught by Demetrescu (see col. 2, lines 25-31).

Regarding Claim 5, the combination of Bodin and Demetrescu discloses every limitation claimed, as applied above (see claim 3), in addition Bodin further discloses the method as claimed in claim 3, wherein

Art Unit: 2686

the mobile station (MS) receives from the radio communications system a command to initiate the handover procedure, which command contains information about the second transmitting/receiving unit (BTS2) and identifies the handover procedure (see col. 6, lines 28-32; Fig. 7),

the radio communications system transmits information about the handover procedure to the second transmitting/receiving unit (BTS2) (see col. 6, lines 32-40; Fig. 7), and

further transmitting/receiving units (BTS) which receive the handover signaling message from the mobile station (MS) check whether the code word contained therein has a value matching the handover code and, if the value matches the handover code, the further transmitting/receiving units reject the handover signaling message (see col. 7, lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines16-22; Fig. 1), where the MS transmits messages to the neighboring base stations for handoff and the message is checked for the correct control data.

Regarding Claim 6, the combination of Bodin and Demetrescu discloses every limitation claimed, as applied above (see claim 4), in addition Bodin further discloses the method as claimed in claim 4, wherein

the mobile station (MS) receives from the radio communications system a command to initiate the handover procedure, which command contains information about the second transmitting/receiving unit (BTS2) and identifies the handover procedure (see col. 6, lines 28-32; Fig. 7),

the radio communications system transmits information about the handover procedure to the second transmitting/receiving unit (BTS2) (see col. 6, lines 32-40; Fig. 7), and

Art Unit: 2686

Page 11

further transmitting/receiving units (BTS) which receive the handover signaling message from the mobile station (MS) check whether the code word contained therein has a value matching the handover code and, if the value matches the handover code, the further transmitting/receiving units reject the handover signaling message (see col. 7, lines 1-6; col. 6, lines 5-9,43-50; col. 5, lines16-22; Fig. 1), where the MS transmits messages to the neighboring base stations for handoff and the message is checked for the correct control data.

Regarding **Claim 8**, the combination of Bodin and Demetrescu discloses every limitation claimed, as applied above (see claim 6), in addition Bodin further discloses the method as claimed in claim 6, wherein at least one of the transmitting/receiving units (BTS) is a base station (BTS) (see col. 5, lines 16-22; Figs. 1, 7-8).

Art Unit: 2686

Conclusion

Page 12

7. Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Willie J. Daniel, Jr. whose telephone number is (703) 305-

8636. The examiner can normally be reached on 7:30-4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Marsha D. Banks-Harold can be reached on (703) 305-4379. The fax phone

number for the organization where this application or proceeding is assigned is 703-872-

9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published

applications may be obtained from either Private PAIR or Public PAIR. Status information

for unpublished applications is available through Private PAIR only. For more information

about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access

to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197

(toll-free).

WJD,JR

18 November 2004

Mousha O Bamb Hard

MARSHA D. BANKS-HAROLD SUPERVISORY PATENT EXAMINER

TECHNOLOGY CENTER 2600